

OB18-14	DG18-14(A)	DN18-14	DP18-14	$L = 370 \pm 5 (-17,5) \text{ mm}$ $D = 180 \pm 2, \text{ Kalotte}$ $D_n = 169 \text{ mm}$
---------	------------	---------	---------	--

<p>ps = sy      pk = sy</p>	Betriebswerte		max.	$I_{k \text{ max}} = 0,2 \text{ mAeff}$						
	$U_{a2} = 4$ (=g5)	$U_{a1} = 2000$ (=g2,4)	$U_g =$	$U_{g5} =$	$U_{g3} = 400 \dots 600$	$-U_{g10} = 45 \dots 85$	$A_{fpk} = 26,5 \dots 31,5$	$A_{fps} = 31,5 \dots 37,5$	$6 \text{ kV}$ $3000 \text{ V}$ $1000^{\circ} \text{ V}$ $1500 \text{ V}$ $250^{\circ} \text{ V}$ $\text{V/cm}$ $\text{V/cm}$	$U_{a2/a1 \text{ max}} = 2$ $U_{a1/p \text{ max}} = 750 \text{ Vs}$ $^{\circ} +0V, +0Vs$
	$U_{a1} = 2000$ (=g2,4)	$U_g =$	$U_{g5} =$	$U_{g3} = 400 \dots 600$	$-U_{g10} = 45 \dots 85$	$A_{fpk} = 26,5 \dots 31,5$	$A_{fps} = 31,5 \dots 37,5$	$6 \text{ kV}$ $3000 \text{ V}$ $1000^{\circ} \text{ V}$ $1500 \text{ V}$ $250^{\circ} \text{ V}$ $\text{V/cm}$ $\text{V/cm}$	$U_{a2/a1 \text{ max}} = 2$ $U_{a1/p \text{ max}} = 750 \text{ Vs}$ $^{\circ} +0V, +0Vs$	
	$U_{a1} = 2000$ (=g2,4)	$U_g =$	$U_{g5} =$	$U_{g3} = 400 \dots 600$	$-U_{g10} = 45 \dots 85$	$A_{fpk} = 26,5 \dots 31,5$	$A_{fps} = 31,5 \dots 37,5$	$6 \text{ kV}$ $3000 \text{ V}$ $1000^{\circ} \text{ V}$ $1500 \text{ V}$ $250^{\circ} \text{ V}$ $\text{V/cm}$ $\text{V/cm}$	$U_{a2/a1 \text{ max}} = 2$ $U_{a1/p \text{ max}} = 750 \text{ Vs}$ $^{\circ} +0V, +0Vs$	
	$U_{a1} = 2000$ (=g2,4)	$U_g =$	$U_{g5} =$	$U_{g3} = 400 \dots 600$	$-U_{g10} = 45 \dots 85$	$A_{fpk} = 26,5 \dots 31,5$	$A_{fps} = 31,5 \dots 37,5$	$6 \text{ kV}$ $3000 \text{ V}$ $1000^{\circ} \text{ V}$ $1500 \text{ V}$ $250^{\circ} \text{ V}$ $\text{V/cm}$ $\text{V/cm}$	$U_{a2/a1 \text{ max}} = 2$ $U_{a1/p \text{ max}} = 750 \text{ Vs}$ $^{\circ} +0V, +0Vs$	
	$U_{a1} = 2000$ (=g2,4)	$U_g =$	$U_{g5} =$	$U_{g3} = 400 \dots 600$	$-U_{g10} = 45 \dots 85$	$A_{fpk} = 26,5 \dots 31,5$	$A_{fps} = 31,5 \dots 37,5$	$6 \text{ kV}$ $3000 \text{ V}$ $1000^{\circ} \text{ V}$ $1500 \text{ V}$ $250^{\circ} \text{ V}$ $\text{V/cm}$ $\text{V/cm}$	$U_{a2/a1 \text{ max}} = 2$ $U_{a1/p \text{ max}} = 750 \text{ Vs}$ $^{\circ} +0V, +0Vs$	
	$U_{a1} = 2000$ (=g2,4)	$U_g =$	$U_{g5} =$	$U_{g3} = 400 \dots 600$	$-U_{g10} = 45 \dots 85$	$A_{fpk} = 26,5 \dots 31,5$	$A_{fps} = 31,5 \dots 37,5$	$6 \text{ kV}$ $3000 \text{ V}$ $1000^{\circ} \text{ V}$ $1500 \text{ V}$ $250^{\circ} \text{ V}$ $\text{V/cm}$ $\text{V/cm}$	$U_{a2/a1 \text{ max}} = 2$ $U_{a1/p \text{ max}} = 750 \text{ Vs}$ $^{\circ} +0V, +0Vs$	
	$U_{a1} = 2000$ (=g2,4)	$U_g =$	$U_{g5} =$	$U_{g3} = 400 \dots 600$	$-U_{g10} = 45 \dots 85$	$A_{fpk} = 26,5 \dots 31,5$	$A_{fps} = 31,5 \dots 37,5$	$6 \text{ kV}$ $3000 \text{ V}$ $1000^{\circ} \text{ V}$ $1500 \text{ V}$ $250^{\circ} \text{ V}$ $\text{V/cm}$ $\text{V/cm}$	$U_{a2/a1 \text{ max}} = 2$ $U_{a1/p \text{ max}} = 750 \text{ Vs}$ $^{\circ} +0V, +0Vs$	
	$U_{a1} = 2000$ (=g2,4)	$U_g =$	$U_{g5} =$	$U_{g3} = 400 \dots 600$	$-U_{g10} = 45 \dots 85$	$A_{fpk} = 26,5 \dots 31,5$	$A_{fps} = 31,5 \dots 37,5$	$6 \text{ kV}$ $3000 \text{ V}$ $1000^{\circ} \text{ V}$ $1500 \text{ V}$ $250^{\circ} \text{ V}$ $\text{V/cm}$ $\text{V/cm}$	$U_{a2/a1 \text{ max}} = 2$ $U_{a1/p \text{ max}} = 750 \text{ Vs}$ $^{\circ} +0V, +0Vs$	

$U_f / I_f$	$6,3 \text{ V} / 0,3 \text{ A}$	$U_{fk \text{ max}} = \pm 125 \text{ V}$	$U_f (\text{Anheiz}) \text{ max} = 9,5 \text{ V}$
Socket:	Dh 60 a (14-2)	$C_{g1} = 7$	$C_{k} = 7$
		$C_{pk} = 4,7$	$C_{ps} = 5,4$
		$C_{pk1/2} = 1,7$	$pF$