



DESCRIPTION AND RATING

25AV5-GA Beam Pentode. Identical to the 6AV5-GA except for heater ratings. Refer to the 6AV5-GA Description and Rating sheet for complete data.

25AX4-GT Diode. Identical to the 6AX4-GT except for heater ratings. Refer to the 6AX4-GT Description and Rating sheet for complete data.

25BQ6-GA Beam Pentode. Identical to the 6BQ6-GA except for heater ratings. Refer to the 6BQ6-GA Description and Rating sheet for complete data.

25BQ6-GTB Beam Pentode. Identical to the 6BQ6-GTB except for heater ratings listed below. Refer to the 6BQ6-GTB Description and Rating sheet for complete data.

Heater Voltage, AC or DC	25.0	Volts
Heater Current	0.3	Amperes

25C5 Beam Pentode. Identical to the 50C5 except for heater ratings and addition of a controlled heater-warm-up characteristic. Refer to the 50C5 Description and Rating sheet for complete data.

25CA5 Beam Pentode. Identical to the 6CA5 except for heater ratings. Refer to the 6CA5 Description and Rating sheet for complete data.

25CD6-GB Beam Pentode. Identical to the 6CD6-GA except for heater ratings and addition of a controlled heater-warm-up characteristic. Refer to the 6CD6-GA Description and Rating sheet for complete data.

25CU6 Beam Pentode. Identical to the 6CU6 except for heater ratings. Refer to the 6CU6 Description and Rating sheet for complete data.

