

3DK6 THROUGH 3FS5

DESCRIPTION AND RATING

3DK6

3DK6 Sharp-Cutoff Pentode. The 3DK6 is a miniature, sharp-cutoff pentode designed for use as a wide-band radio-frequency or intermediate-frequency amplifier in television receivers.

Except for heater characteristics, the 3DK6 is identical to the 6DK6.

GENERAL

ELECTRICAL

Cathode - Coated Unipotential

Heater Characteristics and Ratings

Heater Voltage, AC or DC*	3.15	Volts
Heater Current \S	0.6±0.04	Amperes
Heater Warm-up Time, Average \P	11	Seconds

3DT6

3DT6 Sharp-Cutoff Pentode. The 3DT6 is a miniature, sharp-cutoff, dual-control pentode primarily intended for use as an FM detector in television receivers.

Except for heater characteristics, the 3DT6 is identical to the 6DT6.

GENERAL

ELECTRICAL

Cathode - Coated Unipotential

Heater Characteristics and Ratings

Heater Voltage, AC or DC*	3.15	Volts
Heater Current \S	0.6±0.04	Amperes
Heater Warm-up Time, Average \P	11	Seconds

3DZ4

3DZ4 Triode. The 3DZ4 is a miniature, medium-mu triode designed for use as a UHF oscillator in television receivers.

Except for heater characteristics, the 3DZ4 is identical to the 6DZ4.

GENERAL

ELECTRICAL

Cathode - Coated Unipotential

Heater Characteristics and Ratings

Heater Voltage, AC or DC \ddagger	3.2	Volts
Heater Current \S	0.45±0.03	Amperes
Heater Warm-up Time, Average \P	11	Seconds

The tubes and arrangements disclosed herein may be covered by patents of General Electric Company or others. Neither the disclosure of any information herein nor the sale of tubes by General Electric Company conveys any license under patent claims covering combinations of tubes with other devices or elements. In the absence of an

express written agreement to the contrary, General Electric Company assumes no liability for patent infringement arising out of any use of the tubes with other devices or elements by any purchaser of tubes or others.

3FS5

3FS5 "Shadow-grid" Beam Pentode. The 3FS5 is a miniature tube, similar in construction to a beam pentode, with an internally connected grid between the control grid and the screen grid, which serves to reduce the ratio of screen current to plate current. The tube is designed for use as a radio-frequency amplifier in VHF television receivers.

Except for heater characteristics, the 3FS5 is identical to the 6FS5.

GENERAL

ELECTRICAL

Cathode - Coated Unipotential

Heater Characteristics and Ratings

Heater Voltage, AC or DC†	2.9	Volts
Heater Current§	0.45±0.03	Amperes
Heater Warm-up Time, Average¶.	11	Seconds

NOTES

- * Heater voltage for a bogey tube at $I_f = 0.6$ amperes.
- † Heater voltage for a bogey tube at $I_f = 0.45$ amperes.
- § The equipment designer should design the equipment so that heater current is centered at the specified bogey value, with heater supply variations restricted to maintain heater current within the specified tolerance.
- ¶ The time required for the voltage across the heater to reach 80 percent of the bogey value after applying 4 times the bogey heater voltage to a circuit consisting of the tube heater in series with a resistance equal to 3 times the bogey heater voltage divided by the bogey heater current.