

Half-Wave Mercury-Vapor Rectifier

GENERAL DATA


Electrical:^a

Filament, Coated:		
Voltage (AC)	2.5	volts
Current at 2.5 volts.	7 ± 1	amp
Minimum heating time prior		
to tube conduction.	20	sec
Typical Anode Starting Voltage.	13	volts
Peak Tube Voltage Drop at anode amperes = 8	12	volts

Mechanical:

Operating Position.	Vertical, base down
Maximum Overall Length.	6-3/8"
Maximum Diameter.	2-1/16"
Weight (Approx.).	4 oz
Bulb.	ST16
Cap.	Medium (JEDEC No.C1-5)
Socket.	Small 4-Contact
Base.	Medium-Shell Small 4-Pin with Bayonet (JEDEC No.A4-10)
Basing Designation for BOTTOM VIEW.	4AU

Pin 1 - Filament
Pin 2 - Filament
Pin 3 - Filament



Pin 4 - Filament
Cap - Anode

Thermal:

Type of Cooling	Convection
Temperature Rise of Condensed Mercury to	
Equilibrium Above Ambient	
Temperature (Approx.)	30 °C

HALF-WAVE RECTIFIER^a

Maximum and Minimum Ratings, Absolute-Maximum Values:

For power-supply frequency of 60 cps

PEAK INVERSE ANODE VOLTAGE.	2000 max.	volts
ANODE CURRENT:		
Peak.	10 max.	amp
Average ^b	2.5 max.	amp
Fault	250 max.	amp
CONDENSED-MERCURY TEMPERATURE		
RANGE (Operating)	+35 to +80	°C

^a with circuit returns to filament-transformer center-tap.

^b Averaged over any interval of 5 seconds maximum.

