




INDUSTRIAL MULTIPLIER PHOTOTUBES

TYPE:

6362



GENERAL CHARACTERISTICS

ELECTRICAL DATA

	Min.	Avg.	Max.	Units
Spectral response		511		
Cathode luminous sensitivity at 210 volts, 0 cycles between cathode and all other electrodes	30	50		$\mu\text{A}/\text{lumen}$
Anode luminous sensitivity 105 volts/stage, 0 cycles	3	7.5		A/lumen
Cathode sensitivity at maximum response at 210 volts between cathode and all other electrodes045		$\mu\text{A}/\mu\text{W}$
Anode dark current at 105 volts/stage (25°C)05	μA
Current amplification at 105 volts/stage		150,000		
Wavelength at maximum response		4400 \pm 500		Angstroms
Wavelength at 10% of maximum response on long wavelength side		6125 \pm 275		Angstroms
Wavelength at 10% of maximum response on short wavelength side		3250 \pm 250		Angstroms

MECHANICAL DATA

Window dimensions, minimum	$\frac{1}{2}$			In. Dia.
Tube Diameter	$\frac{3}{4} \pm \frac{1}{32}$			In.
Overall Length	$4\frac{7}{8} \pm \frac{1}{4}$			In.
Base — Resin (potted) flexible leads				
Mounting Position	Any			
Window index of refraction	1.5			

MAXIMUM RATINGS

Peak cathode current (Note 1)	10	μA
Average anode current (Note 2)	1	mA
Peak anode current	5	mA
Average anode dissipation (Note 2)	0.5	W
Peak anode dissipation	2.0	W
Supply voltage between anode and cathode (DC or peak AC)	1300	Volts
Supply voltage between last dynode and anode (DC or peak AC)	125	Volts
Supply voltage between cathode and 1st dynode (DC or peak AC)	250	Volts
Ambient Temperature	75	$^{\circ}\text{C}$

NOTES

1. The cathode current given here is that current at which the response of the cathode current ceases to be a linear function of the light intensity because of cathode resistance. In general, the cathode current must be kept well below this value in order to satisfy the maximum ratings of the anode current.
2. Averaged over a 30 second interval maximum.

RECOMMENDED ACCESSORY: MU-METAL SHIELD DUMONT P/N 243-2

FEATURES

- S11 Response
- 10 Dynode Stages
- $\frac{3}{4}$ Inch Diameter
- Silver Magnesium Dynodes
- Potted Base for:
 - a. Moisture Resistance
 - b. Shock Resistance
 - c. Socket Elimination
 - d. Noise Free Connections
- Comparable Performance with Large Diameter Tubes
- Maximum Stability at High Voltages
- Small Size for Limited Space Use


APPLICATIONS

- Scintillation Probes
- Analysis Low Level Light Sources
- Oil Exploration
- Spectroscopy

3.9



INDUSTRIAL TUBE SALES DEPARTMENT
750 Bloomfield Avenue
Clifton, New Jersey, U.S.A.




- BOTTOM VIEW OF BASE**
- | PIN NO. | ELEMENT |
|---------|--------------------------------------|
| 1 | DYNODE NO.1 |
| 2 | DYNODE NO.3 |
| 3 | DYNODE NO.5 |
| 4 | DYNODE NO.7 |
| 5 | DYNODE NO.9 |
| 6 | ANODE |
| 7 | DYNODE NO.10 |
| 8 | DYNODE NO.8 |
| 9 | DYNODE NO.6 |
| 10 | DYNODE NO.4 |
| 11 | DYNODE NO.2 |
| 12 | CATHODE- FOCUSING ELECTRODE (SHIELD) |

NOTE: PINS 1 TO 11 HAVE BLACK INSULATION
PIN 12 HAS RED INSULATION.

POTTED SECTION

OUTLINE DRAWING TYPE 6362



SPECTRAL RESPONSE OF 511 PHOTOCATHODE

