

Color Television Type



VHF OSCILLATOR and MIXER

6HG8/ECF86

4HG8, 5HG8/LCF86,
7HG8/PCF86, 8HG8

Medium Mu Triode and Sharp Cutoff Pentode

Construction Miniature T-6½
 Base Button 9 Pin, E9-1
 Basing 9MP
 Outline 6-2
 Maximum Diameter 0.875 In.
 Maximum Seated Height 1.937 In.
 Maximum Overall Height 2.187 In.



ELECTRICAL DATA

HEATER OPERATION

	8HG8	7HG8/ PCF86	5HG8/LCF86	4HG8	6HG8/ ECF86
Heater Voltage.....	8.0	7.2	5.3	4.5	6.3 Volts
Heater Current	300	300	450	600	340 Ma
Heater Warm-up Time	—	—	11	11	— Seconds
Maximum Heater-Cathode Voltage					
Heater Negative with Respect to Cathode					
Total DC and Peak.....					200 Volts
Heater Positive with Respect to Cathode					
DC					100 Volts
Total DC and Peak.....					200 Volts

DIRECT INTERELECTRODE CAPACITANCES (Unshielded)

Triode Section

Grid to Plate	2.0 Pf
Input: g to (h + k, Pk, Pg3, IS)	2.4 Pf
Output: p to (h + k, Pk, Pg3, IS)	1.1 Pf

Pentode Section

Grid No. 1 to Plate (Max.).....	0.020 Pf
Input: g1 to (h + k, Tk, g3, IS + g2)	6.0 Pf
Output: p to (h + k, Pk, Pg3, IS + g2)	3.5 Pf
Grid No. 1 to Grid No. 2	1.7 Pf

Coupling

Triode Grid to Pentode Plate (Max.)	0.014 Pf
Pentode Grid No. 1 to Triode Plate (Max.)	0.01 Pf
Pentode Plate to Triode Plate (Max.)	0.14 Pf
Pentode Grid No. 1 to Triode Grid (Max.)	0.01 Pf

RATINGS (Design Maximum Rating System)

	Triode Section	Pentode Section
Plate Voltage (Max.)	125	250 Volts
Grid No. 2 Supply Voltage (Max.)	—	250 Volts
Grid No. 2 Voltage	See Rating Chart (Gen. Info. Sec.)	
Positive Grid No. 1 Voltage (Max.)	0	0 Volt
Plate Dissipation (Max.)	1.9	2.2 Watts
Grid No. 2 Dissipation (Max.)	—	0.55 Watts
Cathode Current (Max.).....	16.5	20 Ma
Grid No. 1 Circuit Resistance (Max.)	0.5	— Megohm
Fixed Bias (Max.)	—	0.25 Megohm
Cathode Bias (Max.)	—	0.5 Megohm

The spacing between the control grids and cathodes are of such a low order of magnitude as to preclude the use of excessive voltages between these elements in commercial tube checkers and shorts indicating devices, particularly where the tube is mechanically excited. The DC or peak AC voltage applied between each sections control grid and cathode must not exceed 30 volts for the pentode or 50 volts for the triode.

RATINGS (Design Maximum Rating System)

Horizontal Deflection Amplifier⁽¹⁾

Plate Voltage (boost + DC power supply) (Max.)	770 Volts
Grid No. 2 Voltage (Max.)	220 Volts
Plate Dissipation (Max.)	24 Watts
Grid No. 2 Dissipation (Max.)	6.0 Watts
Grid No. 2 Dissipation (warm up surge) (Max.) ⁽²⁾	12 Watts
Average Cathode Current (Max.).....	280 Ma
Peak Cathode Current (Max.)	1000 Ma
Peak Positive Plate Voltage (Max.)	7000 Volts
Peak Negative Plate Voltage (Max.)	1500 Volts
Peak Negative Grid No. 1 Voltage (Max.)	330 Volts
Grid No. 1 Circuit Resistance (Max.)	1.0 Megohm
Bulb Temperature (at Hottest Point) (Max.)	240 °C
DC Grid No. 3 Voltage (Max.)	70 Volts

CHARACTERISTICS AND TYPICAL OPERATION

Plate Voltage	20	40	60	135 Volts
Grid No. 2 Voltage	110	110	135	135 Volts
Grid No. 1 Voltage	0	0	0	-22 Volts
Grid No. 3 Voltage	—	—	—	0 Volt
Plate Current	240 ⁽³⁾	400 ⁽³⁾	540 ⁽³⁾	80 Ma
Grid No. 2 Current	160 ⁽³⁾	42 ⁽³⁾	48 ⁽³⁾	5.5 Ma
Triode Amplification Factor.....	—	—	—	4.2
Transconductance	—	—	—	10,000 μmhos
Plate Resistance.....	—	—	—	5000 Ohms
Grid No. 1 Voltage (Approx.) for Ib = 1 Ma (Ep = 4.5 KV)	—	—	—	-70 Volts

NOTES:

- (1) For operating in a 525 line, 30 frame system as described in "Standards of Good Engineering Practice for Television Broadcast Stations, Federal Communications Commission," the duty cycle of the voltage pulse must not exceed 15% of one horizontal scanning cycle.
- (2) Surge not to exceed 15 seconds duration.
- (3) Instantaneous Values.