

MARCONI VALVES

MARCONI VALVES

for use with 4-volt Accumulator

TYPES DEH 410 AND DEL 410



TYPE DEH 410

DULL EMITTER, RESISTANCE CAPACITY
AMPLIFYING AND DETECTOR VALVE.

A highly efficient dull emitter valve, having a very high "amplification factor" making it suitable for the following purposes :

1. In resistance capacity coupled amplifiers, except in the last stages, where types DEL 410, DEP 410 or P 425 should be used.
2. As a detector valve, either with grid leak and condenser or for anode bend rectification.
3. In high frequency amplifiers, where a circuit with some form of stabilising or damping is employed.

The maximum filament voltage is 4.0 and this figure should not be exceeded.

Approximate Overall Dimensions,
103 x 46 mm.

TYPE DEH 410

Fil. Volts 4.0 max.
Fil. Current 0.1 amps.
Anode Volts 150 max.
*Amp. Factor 40
*Impedance 60,000 ohms.
*Normal Slope .66 Ma/v.
*At Anode Volts 100

Grid Volts 0

Price, 10/6

TYPE DEL 410

Fil. Volts 4.0 max.
Fil. Current 0.1 amps.
Anode Volts 150 max.
*Amp. Factor 15
*Impedance ... 8,500 ohms.
*Normal Slope 1.76 Ma/v.
*At Anode Volts 100

Grid Volts 0

Price, 10/6

TYPE DEL 410

DULL EMITTER, GENERAL PURPOSE VALVE.

A highly efficient dull emitter valve, having characteristics which make it very suitable for the following purposes :

1. In high frequency amplifiers where a circuit with some method of stabilising or damping is employed.
2. As a detector valve using grid leak and condenser.
3. In transformer or choke-coupled low frequency amplifiers, in all stages except the last, where a DEP 410 or P 425 power valve should be used.

The maximum filament voltage is 4.0 and this figure should not be exceeded.

The valve in the purple box