

| Type Herst. | EBF 1 Ph | EBF 2 Va, Po, TE | EBF 2 G Ph, TsP |
|------------------|----------------------|--------------------------|-----------------------|
| U_f | 6,3 | 6,3 | |
| I_f | 0,3 | 0,2 | |
| Heizart | B~ | B≅ | |
| Verw. Kbn-Lg. | Diode, HF-Verstärker | | |
| Kbn-Ø | — | 92 | |
| | — | 33 | |
| U_a | 250 | 250 | |
| U_{g3} | 200 ¹⁴⁾ | 200 ¹⁴⁾ | |
| U_{g4} | 0,8 ¹⁵⁾ | 0,8 ¹⁵⁾ | |
| U_{g2} | — | — | |
| U_{g1} | 125 | 100...250 ¹⁶⁾ | |
| U_{g1} | -3 | -2 | -38 |
| I_a | 9 | 5 | — |
| I_{g2} | 2,3 | 1,6 | — |
| S | 1,1 | 1,8 | 0,018 |
| D | — | — | — |
| R_{ξ} | 650 | 1300 | >10000 ¹⁷⁾ |
| R_{ξ} | 0,33 | 0,3 | |
| R_a | — | — | |
| R_{g3} | — | 95 | |
| $U_{g1} \sim$ | — | — | |
| V | 730 | 2200 | |
| $N_a \sim$ | — | — | |
| U_b max | 200 | 300 | |
| U_{g3} max | — | 125 ¹⁸⁾ | |
| N_a max | — | 1,5 | |
| N_{g3} max | — | 0,3 | |
| R_{g1} max | — | 3 | |
| $c_{g/a}$ | 2 | <0,002 | |



EBF 1



EBF 2



EBF 2 G