



Current Equipment Types



TYPE VR75/30
 TYPE VR105/30
 TYPE VR150/30
 (OCTAL BASE)



VR75/30
 VR105/30
 VR150/30

VOLTAGE REGULATORS

CHARACTERISTICS

TYPE VR75/30

Minimum Starting Voltage	100 volts
Nominal Operating Voltage	75 volts
Minimum Operating Current	5 mA
Maximum Operating Current	40 mA
Maximum Peak Current	100 mA
Regulation (minimum to maximum currents)...	6.5 volts

TYPE VR105/30

Minimum Starting Voltage	135 volts
Nominal Operating Voltage	105 volts
Minimum Operating Current	5 mA
Maximum Operating Current	40 mA
Maximum Peak Current	100 mA
Regulation (minimum to maximum currents)...	4 volts

TYPE VR150/30

Minimum Starting Voltage	180 volts
Nominal Operating Voltage	150 volts
Minimum Operating Current	5 mA
Maximum Operating Current	40 mA
Maximum Peak Current	100 mA
Regulation (minimum to maximum currents)...	5.5 volts

The series resistor fitted between regulator valve and supply voltage must be such that under no-load conditions the current rating of the valve is not exceeded.

Note : Type VR75/30 is exactly equivalent to type OA3
 Type VR105/30 is exactly equivalent to type OC3
 Type VR150/30 is exactly equivalent to type OD3

Type VR75/30 is a commercial equivalent to the CV3798
 Type VR105/30 is a commercial equivalent to the CV686
 Type VR150/30 is a commercial equivalent to the CV216